

## Length Rite Systems

## Accurate Length Measurement for Wire & Cable



The Length Rite 300 is an accurate, easy-to-maintain length measuring device that enables you to reduce time and cost in your wire harness facilities.

What's more, the Length Rite 300 has the lightweight and portable design to benefit wire suppliers, wire harness manufacturers, or even on-site electricians.

The Length Rite 300 can be integrated as a cut to length system perfect for generating batch jobs for wire harness manufacturing.

With the optional PLC controller, the LR300 has dedicated large character displays for both length count and line speed, giving operators all the information they need at a glance. Furthermore, information can be sent to the PLC for further processing.

The Optional PLC control system for the Length Rite 300 comes preprogrammed with two contact closures that indicate when preset lengths are exceeded.

## **FEATURES**

- > Lightweight and portable design
- > Highly accurate +/- 0.2%
- > Easy belt removal and installation
- > Industry leading 600 ppr measurement

- > Dedicated, easy to read 6 digits display for length count
- State of the art, remote mountable electronic system, allowing for 2 inputs and 5 outputs
- Optional pneumatic raise and lower of the encoder caterpillar assembly





## **SPECIFICATIONS**

- > Maximum Speed: Dimensions: 7" x 6" x 16" (L x W x H) 100 feet / minute 180 mm x 150 mm x 400 mm (L x W x H) 30 meters / minute > Wire and Cable Size: > Power: 0.025" - 0.500" 115 VAC 50/60 Hz 0.6 mm - 12.7 mm 220 VAC 50/60 Hz Measurement Accuracy: +/- 0.2 % Count Display: 6 digits > Weight: > Calibration: 7 lbs. Easily programmable using keypad (PLC) 3.2 kg Outputs: (PLC Controller Option) Measurement Units: Counter & line speed Metric Contact closure: exceed input length count 1 Footage Contact closure: exceed input length count 2 Both metric and footage with PLC controller > Inputs: Remote reset Reset: Push button
- Speed Display (PLC): 6 digits
- > Air: 50 psi supply required with pneumatic option

> Belt: Polyurethane, steel reinforced, incompressible belt

> Mount: Benchtop mounting holes



**↓** +1 905 479 2614 **+1** 905 479 2636

info@taymer.comwww.taymer.com

Taymer International Inc. - 208 Telson Road Markham, ON L3R 1E6 - CANADA